

CLASS "A" COMPOSITION
SHINGLE ROOFING OVER
30# FELT OVER 15/32 OSB
ROOF SHEATHING

CHIMNEY TO BE 24" ABOVE
ANY POINT WITHIN 10' HORIZONTAL

5/4X4 LP SMART TRIM
HARDPLANK LAP SIDING
NER REPORT #124 OVER
TYPAR HOUSEWRAP OVER
3/8" OSB SHEATHING MIN.

5/4X6 FASCGA

6X14 GAL METAL FOUNDATION
VENTS EQUALLY SPACED TO
ALLOW FOR CROSS
VENTILATION(TYP)

LANDING AT DOORS SHALL BE A MINIMUM OF
THE WIDTH OF THE DOOR, AND EXTEND IN THE
DIRECTION OF TRAVEL. A MIN OF 36". A 36" HIGH
GUARDRAIL WITH NO OPENING LARGE ENOUGH FOR A
4" SPHERE TO PASS THROUGH IS REQUIRED FOR ALL
ALL LANDINGS MORE THAN 30" ABOVE THE ADJOINING
LEVEL OR GROUND. A HAND RAIL IS REQUIRED
FOR STAIRS WITH FOUR (4) OR MORE RISERS.

REAR ELEVATION

SCALE 1/4" = 1'-0"

14X24 GABLE VENT

5/4X6 L-P SMART TRIM
BARGE & FASCGA

27'-9"

RIGHT ELEVATION

SCALE 1/4" = 1'-0"

REVISIONS BY

PACIFIC MODERN HOMES
P.O. BOX 670
ELK GROVE, CA.
95759-9514
PHONE: (916) 685-9514



ELEVATIONS

PAGE TITLE

RESIDENCE FOR:

PRE-
ENGINEERED
SPRINGFIELD

DATE

SCALE
1/4" = 1'-0"

TOWN BY

TOWN TO

SHEET:

2